



GREEN Series HMI

GH043U2/GH043EU2

Product Features :

- 4.3", high-definition display, 16.77 million true colors;
- Double USB Host design, USB interface device or U disk can be connected before and after;
- The front panel protection level meets IP65 certification requirements;
- Built-in isolated power to enhance reliability;
- Main board three-defence treatment to effectively deal with complex environment.




The GREEN series cooperates with new generation free configuration software: **Kinco DTools**.

It supports eight languages versions of Chinese, Traditional Chinese, English, Korean, Germany, Russia, Arabic and Turkey.

The configuration design content supports all fonts installed in computer system.

It supports cloud monitoring. VNC achieves interoperation between HMI and HMI, HMI and PC, mobile phones (or other terminals), supports convenient components such as installation, PDF browsing and operating log records for designing guiding interface.

GREEN Series HMI GH043U2/GH043EU2



Type	GH043U2	GH043EU2
Performance specification		
Display size	4.3" TFT	
Display area	95.04(W)x53.86(H)	
Resolution	480*272 pixel	
Display color	16.77M color	
Display angle of view	70/70/50/70(left/right/up/down)	
Contrast ratio	500:1	
Backlight	LED	
Brightness	300cd/m ²	
Backlight life	More than 30000 hours	
Touch panel	4wire precision resistance network(surface hardness 4H)	
CPU	ARM RISC 32Bit 800MHz	
Storage	256MB NAND Flash Memory+128MB DDR3 Memory	
RTC	Built-in	
Memory extension	2 USB Host	2 USB Host + 1 SD Card
Printer port	USB Host*2/Serial port	USB Host*2/Serial port
Ethernet	None	10/100M self-adaption
Program download	USB Slave(Type B)/U disk	USB Slave(Type B) /U disk/Ethernet port
Communication port	COM0:RS232/RS485/RS422; COM2:RS232	COM0:RS232/RS485/RS422; COM2:RS232
Serial port isolation	None	None
Electrical specification		
Rated voltage	DC10.8V ~ DC28V, built-in isolated power supply	
Rated power	3.5W	
Allowable loss of power	<3ms	
Insulation resistance	Greater than 50MΩ@500V DC	
Hi-pot test	500 VAC 1minute	
Structure specification		
PCB	exquisite spraying	
Shell material	Engineering plastic	
Dimensions(mm)	154mm*89mm*60mm	
Cutout size(mm)	146mm*81mm	
Weight	0.4Kg	
Environment specification		
Temperature working	-25 ~ 55°C	
Humidity working	10 ~ 90%RH(non-condensing)	
Storage temperature	-25 ~ 60°C	
Storage humidity	10 ~ 90%RH(non-condensing)	
Sine vibration test	10~500Hz ,30m/s ² , X,Y,Z direction/hour	
Cooling method	Natural air cooling	
Certification		
Panel protection grade	Conforming to Ip65 certification (4208—93)	
CE authentication	Comply with EN61000-6-4:2007+A1:2011,EN61000-6-2:2005	
Software		
Configuration software	Kinco DTools V4.1and above	

Dimensions(mm)

