

GREEN Series HMI

G070/G070E/G070E-CAN

Product Features :

- Industrial grade CPU, 800MHz, 128M DDR3;
- 7", high-definition display, 16.77 million true colors;
- Three proofing spraying + Built-in isolated power to enhance reliability;
- Three serial ports for different levels of requirements;
- Support CANopen;
- Sealing design of buckle for waterproof and oil resistance.



The GREEN series cooperates with new generation free configuration software: **Kinco DTools**.


It supports eight languages versions of Chinese, Traditional Chinese, English, Korean, Germany, Russia, Arabic and Turkey.

The configuration design content supports all fonts installed in computer system.

It supports cloud monitoring. VNC achieves interoperation between HMI and HMI, HMI and PC, mobile phones (or other terminals), supports convenient components such as installment, PDF browsing and operating log records for designing guiding interface.

G070/G070E/G070E-CAN

- Three proofing spraying + Built-in isolated power to enhance reliability
- Three serial ports for different levels of requirements
- Support CANopen



Model	G070	G070E	G070E-CAN
Performance specification			
Display size	7" TFT		
Display area	154.08mm(W)x85.92mm(H)		
Resolution	800*480 pixel		
Display color	16.7M color		
Display angle of view	70/70/60/70(left/right/up/down)		
Contrast ratio	500:1		
Backlight	LED		
Brightness	400cd/m ²		
Backlight life	More than 30000 hours		
Touch panel	4 line precision resistance network (surface hardness 4H)		
CPU	ARM RISC 32Bit 800MHz		
Storage	128MB NAND Flash Memory+128MB DDR3 Memory		
RTC	Built-in		
Extensible memory	1 USB Host		
Print port	USB Host/serial port		
Ethernet	None	10/100M self-adaption	10/100M self-adaption
Bus interface	None	None	1*CANopen
Program download	USB Slave (Micro USB)/U disk	USB Slave(Micro USB) /U disk/Ethernet	USB Slave(Micro USB) /U disk/Ethernet
Communication port	COM0:RS232/RS485/RS422; COM1:RS485/RS422;COM2:RS232		
Electrical specifications			
Input power supply	DC12V ~ DC28V,Built-in isolation power supply		
Rated power	3.8W		
Allowable loss of power	<3ms		
Insulation resistance	Over 50MΩ@500V DC		
Hi-pot test	500 VAC 1 minute		
Structure specifications			
PCB spraying	Yes		
Shell material	Engineering plastic		
Shape size	204mm*150mm*37mm		
Cutout size	192mm*138mm		
Weight	0.5Kg		
Environmental specifications			
working Temperature	0 ~ 50°C		
working Humidity	10 ~ 90%RH (non-condensing)		
Storage temperature	-20 ~ 60°C		
Storage humidity	10 ~ 90%RH (non-condensing)		
Sine vibration test	10 ~ 500Hz, 30m/s ² , X, Y, Z direction/hour		
Cooling mode	Natural air cooling		
Product certification			
Panel protection grade	Conforming to IP65 certification(4208—93)		
CE authentication	EN61000-6-4:2007+A1:2011, EN61000-6-2:2005		
Software			
Configuration software	Kinco DTools V3.3 and above		

Mechanical Dimensions (Unit : mm)

