

Annex for

Certification No.: TOS21014559

Test Report Ref. No.: 68.5.51.13.0416.05-Co.01

Model List:

Model	Voltage (V)	Current (A)	Power (W)	Speed (rpm)	Stator (mm)	Rotor (mm)	Stack (mm)	Winding		
								Duplex no.	Diameter (mm)	Turns
SMC130D-0150-20XXX-4HXX-XX	380V AC	4.3	1500	2000	130x130	φ78	40	1	0.74	84
SMH130D-0105-20XXX-4HXX-XX	560	4.3	1050	2000	130x130	φ78	40	3	0.53	56
SMH130D-0105-15XXX-4XXX-XX	560	4.7	1050	1500	130x130	φ78	40	3	0.47	69
SMH130D-0157-20XXX-4HXX-XX	560	6.3	1570	2000	130x130	φ78	60	4	0.55	38
SMH130D-0210-20XXX-4HXX-XX	560	7.6	2100	2000	130x130	φ78	80	3	0.71	31
SMC130D-0200-20XXX-4HXX-XX	380V AC	6	2000	2000	130x130	φ78	60	2	0.67	52
SMH130D-0300-20XXX-4HXX-XX	560	7.9	3000	2000	130x130	φ78	120	4	0.65	27
SMC130D-0300-20XXX-4HXX-XX	380V AC	6.5	3000	2000	130x130	φ78	100	2	0.74	43
SMC130D-0300-30XXX-4HXX-XX	380V AC	6.1	3000	3000	130x130	φ78	80	4	0.55	39
SMC130D-0320-30XXX-4HXX-XX	380V AC	7.1	3140	3000	130x130	φ78	100	4	0.65	28
SMH150D-0230-20XXX-4HXX-XX	560	7.1	2300	2000	150x150	φ92	56	2	0.71	20
SMH150D-0300-20XXX-4HXX-XX	560	8.5	3000	2000	150x150	φ92	84	5	0.53	14
SMH150D-0380-20XXX-4HXX-XX	560	9.3	3800	2000	150x150	φ92	112	6	0.53	12
SMH150D-0460-20XXX-4HXX-XX	560	10.7	4600	2000	150x150	φ92	140	7	0.53	10
SMH180D-0350-15XXX-4HXX-XX	560	10.3	3500	1500	180x180	φ106	76	4	0.71	15
SMH180D-0440-15XXX-4HXX-XX	560	11.9	4400	1500	180x180	φ106	114	5	0.74	11
SMH180D-0600-15XXX-4HXX-XX	560	19.1	6000	1500	180x180	φ106	152	8	0.71	7
SMH180D-0550-15XXX-4XXX-XX	560	13.5	5500	1500	180x180	φ106	152	6	0.74	9
SMH180D-0700-20XXX-4XXX-XX	560	16.7	7000	2000	180x180	φ106	152	8	0.71	7
SMH180D-0750-15XXX-4HXX-XX	560	19.2	7500	1500	180x180	φ106	190	8	0.71	7
SMH180D-0900-20XXX-4HXX-XX	560	21	9000	2000	180x180	φ106	190	10	0.71	6
SMS130D-0150-20XXX-4HXX-XX	380V AC	4.5	1500	2000	130x130	φ78	40	1	0.74	84
SMS130D-0200-20XXX-4HXX-XX	380V AC	6	2000	2000	130x130	φ78	60	2	0.67	52
SMS130D-0300-20XXX-4HXX-XX	380V AC	6.7	3000	2000	130x130	φ78	100	2	0.74	43
SMS130D-0300-30XXX-4HXX-XX	380V AC	6.2	3000	3000	130x130	φ78	80	4	0.55	39
SMH130D-0157-20XXX-4HXX-XX	560	6.3	1570	2000	130x130	φ78	60	4	0.55	37
SMC130D-0320-30XXX-4HXX-XX	380V AC	6.6	3140	3000	130x130	φ78	100	3	0.65	37
SMS130D-0200-20XXX-4HXX-XX	380V AC	6.2	2000	2000	130x130	φ78	60	2	0.67	52
SMH180D-0500-30XXX-4HXX-XX	380V AC	14.8	5000	3000	180x180	φ106	114	11	0.74	5

