


Annex for

Certification No.: TOS21014553

Test Report Ref. No.: 68.4.51.11.0084.08-Co.01

Model List:

Model	Voltage (V)	Current (A)	Power (W)	Speed (rpm)	Stator (mm)	Rotor (mm)	Stack (mm)	Winding		
								Duplex no.	Diameter r(mm)	Turns
SMH60S-0020-30XXX-3LXX-XX	220	1.6	200	3000	60x60	φ32	30	1	0.4	104
SMC60S-0020-30XXX-3LXX-XX	220	1.4	200	3000	60x60	φ32	24	1	0.35	132
SMH60S-0040-30XXX-3LXX-XX	220	3.1	400	3000	60x60	φ32	60	1	0.55	52
SMC60S-0040-30XXX-3LXX-XX	220	2.4	400	3000	60x60	φ32	50	1	0.47	71
SMH80S-0075-30XXX-3LXX-XX	220	3.9	750	3000	80x80	φ42	60	1	0.85	49
SMC80S-0075-30XXX-3LXX-XX	220	3.8	750	3000	80x80	φ42	45	1	0.74	67
SMH80S-0100-30XXX-3LXX-XX	220	6.3	1000	3000	80x80	φ42	80	2	0.71	32
SMC80S-0100-30XXX-3LXX-XX	220	6.2	1000	3000	80x80	φ42	60	2	0.63	42
SMH80S-0075-30XXX-3LXX-XX	220	5	750	3000	80x80	φ42	60	2	0.67	36
SMH110D-0052-10XXX-4LXX-XX	220	3.6	530	1000	110x11	φ63	85	2	0.63	48
SMH110D-0084-20XXX-4LXX-XX	220	4.3	840	2000	110x11	φ63	68	3	0.51	44
SMH110D-0125-30XXX-4LXX-XX	220	6.5	1250	3000	110x11	φ63	68	4	0.55	29
SMH110D-0105-20XXX-4LXX-XX	220	5.9	1050	2000	110x11	φ63	85	4	0.53	30
SMH110D-0126-20XXX-4LXX-XX	220	6.15	1260	2000	110x11	φ63	102	4	0.53	31
SMH110D-0126-30XXX-4LXX-XX	220	7.7	1260	3000	110x11	φ63	68	3	0.71	24
1FL4032-1AF21-1AA1	220	1.2	200	3000	60x60	φ32	30	1	0.38	115
1FL4032-1AF21-1AB1										
1FL4032-1AF21-1AG1										
1FL4032-1AF21-1AH1										
1FL4034-1AF21-1AA1	220	2.4	400	3000	60x60	φ32	60	1	0.53	57
1FL4034-1AF21-1AB1										
1FL4034-1AF21-1AG1										
1FL4034-1AF21-1AH1										
1FL4042-1AF21-1AA1	220	4.3	750	3000	80x80	φ42	60	1	0.9	43
1FL4042-1AF21-1AB1										
1FL4042-1AF21-1AG1										
1FL4042-1AF21-1AH1										
1FL4044-1AF21-1AA1	220	6	1000	3000	80x80	φ42	80	2	0.71	32
1FL4044-1AF21-1AB1										
1FL4044-1AF21-1AG1										
1FL4044-1AF21-1AH1										



Annex for

Certification No.: TOS21014553

Test Report Ref. No.: 68.4.51.11.0084.08-Co.01

Model List:

Model	Voltage (V)	Current (A)	Power (W)	Speed (rpm)	Stator (mm)	Rotor (mm)	Stack (mm)	Winding		
								Duplex no.	Diamete r(mm)	Turns
SMH60S-0010-30XXX-XLXX-XX	220	0.75	100	3000	60x60	φ32	10	1	0.25	196
SMC60S-0010-30XXX-XLXX-XX										
SMS60S-0010-30XXX-XLXX-XX										
SMH60S-0020-30XXX-XLXX-XX	220	1.5	200	3000	60x60	φ32	20	1	0.38	97
SMC60S-0020-30XXX-XLXX-XX										
SMS60S-0020-30XXX-XLXX-XX										
SMH60S-0030-30XXX-XLXX-XX	220	2.2	300	3000	60x60	φ32	30	1	0.44	65
SMC60S-0030-30XXX-XLXX-XX										
SMS60S-0030-30XXX-XLXX-XX										
SMH60S-0040-30XXX-XLXX-XX	220	2.9	400	3000	60x60	φ32	42	1	0.53	49
SMC60S-0040-30XXX-XLXX-XX										
SMS60S-0040-30XXX-XLXX-XX										
SMH60S-0060-30XXX-XLXX-XX	220	4.4	600	3000	60x60	φ32	75	1	0.71	26
SMC60S-0060-30XXX-XLXX-XX										
SMS60S-0060-30XXX-XLXX-XX										
SMH80S-0040-30XXX-XLXX-XX	220	2.1	400	3000	80x80	φ42	24	1	0.55	72
SMC80S-0040-30XXX-XLXX-XX										
SMS80S-0040-30XXX-XLXX-XX										
SMH80S-0060-30XXX-XLXX-XX	220	3.2	600	3000	80x80	φ42	35	1	0.67	49
SMC80S-0060-30XXX-XLXX-XX										
SMS80S-0060-30XXX-XLXX-XX										
SMH80S-0075-30XXX-XLXX-XX	220	4	750	3000	80x80	φ42	42	2	0.51	41
SMC80S-0075-30XXX-XLXX-XX										
SMS80S-0075-30XXX-XLXX-XX										
SMH80S-0100-30XXX-XLXX-XX	220	6.2	1000	3000	80x80	φ42	58	2	0.67	25
SMC80S-0100-30XXX-XLXX-XX										
SMS80S-0100-30XXX-XLXX-XX										
SMS60S-0020-30XXX-3LXX-XX	220	1.4	200	3000	60x60	φ32	24	1	0.35	132
SMS60S-0040-30XXX-3LXX-XX	220	2.4	200	3000	60x60	φ32	50	1	0.47	71
SMS80S-0075-30XXX-3LXX-XX	220	3.8	750	3000	80x80	φ42	45	1	0.74	67
SMS80S-0100-30XXX-3LXX-XX	220	6.2	1000	3000	80x80	φ42	60	2	0.63	42
SMH80S-0100-20XXX-3LXX-XX	220	4	1000	2000	80x80	φ42	120	2	0.61	47
SMH60S-0020-30XXX-3AXX-XX	110	2.7	200	3000	60x60	φ32	30	1	0.55	52
SMH60S-0040-30XXX-3AXX-XX	110	4	400	3000	60x60	φ32	60	1	0.67	35
SMH80S-0075-30XXX-3AXX-XX	110	7.5	750	3000	80x80	φ42	60	3	0.65	25
SMH80S-0100-30XXX-3AXX-XX	110	10	1000	3000	80x80	φ42	80	4	0.65	19

