

## Annex for

Certification No.:TOS21014557

Test Report Ref. No.: 68.5.51.13.0414.06-Co.01

### Model List:

Model	Voltage (V)	Current (A)	Power (W)	Speed (rpm)	Stator (mm)	Rotor (mm)	Stack (mm)	Winding		
								Duplex no.	Diameter (mm)	Turns
SMH40S-0005-30XXX-4LXX-XX	300	0.7	50	3000	40x40	φ20	20	1	0.25	92
SMH40S-0010-30XXX-4LXX-XX	300	1.4	100	3000	40x40	φ20	46	1	0.4	41
SMC130D-0100-20XXX-4LXX-XX	220V AC	4.2	1000	2000	130x130	φ78	24	1	0.71	92
SMH130D-0105-20XXX-4LXX-XX	300	4.2	1050	2000	130x130	φ78	40	3	0.53	57
SMC130D-0150-20XXX-4LXX-XX	220V AC	6.5	1500	2000	130x130	φ78	40	2	0.65	56
SMH130D-0157-20XXX-4LXX-XX	300	6.3	1570	2000	130x130	φ78	60	4	0.55	38
SMH130D-0210-20XXX-4LXX-XX	300	8.4	2100	2000	130x130	φ78	80	4	0.65	28
SMH130D-0300-20XXX-4LXX-XX	300	12	3000	2000	130x130	φ78	100	4	0.71	23
SMC130D-0200-20XXX-4LXX-XX	220V AC	8.2	2000	2000	130x130	φ78	60	4	0.55	38
SMC130D-0320-30XXX-4LXX-XX	220V AC	12.3	3200	3000	130x130	φ78	100	4	0.85	16
SMH40S-0005-30XXX-5LXX-XX	220V AC	0.8	50	3000	40x40	φ17.4	18	1	0.25	104
SMC40S-0005-30XXX-5LXX-XX										
SMS40S-0005-30XXX-5LXX-XX										
SMH40S-0010-30XXX-5LXX-XX	220V AC	1.3	100	3000	40x40	φ17.4	40	1	0.35	54
SMS40S-0010-30XXX-5LXX-XX										
SMC40S-0010-30XXX-5LXX-XX										
SMS130D-0100-20XXX-4LXX-XX	220V AC	4.4	1000	2000	130x130	φ78	24	1	0.71	92
SMS130D-0150-20XXX-4LXX-XX	220V AC	6.8	1500	2000	130x130	φ78	40	2	0.65	56
SMS130D-0200-20XXX-4LXX-XX	220V AC	8.2	2000	2000	130x130	φ78	60	4	0.55	37
SMS130D-0100-30XXX-4LXX-XX	220V AC	4	1000	3000	130x130	φ78	24	1	0.85	63
SMS130D-0150-30XXX-4LXX-XX	220V AC	6.1	1500	3000	130x130	φ78	40	3	0.65	38
SMS130D-0320-25XXX-4LXX-XX	300	13	3200	2500	130x130	φ78	120	7	0.65	16
SMH130D-0105-20XXX-4LXX-XX	300	4.3	1050	2000	130x130	φ78	40	3	0.53	56
SMH130D-0105-20XXX-4LXX-XX	300	5.3	1050	2000	130x130	φ78	40	2	0.71	46
SMC130D-0150-20XXX-4LXX-XX	220V AC	6.8	1500	2000	130x130	φ78	40	2	0.65	56
SMH130D-0157-20XXX-4LXX-XX	300	6.3	1570	2000	130x130	φ78	60	4	0.55	37
SMH130D-0300-20XXX-4LXX-XX	300	12	3000	2000	130x130	φ78	100	4	0.71	22
SMC130D-0200-20XXX-4LXX-XX	220V AC	8.8	2000	2000	130x130	φ78	60	4	0.55	38
SMS130D-0200-20XXX-4LXX-XX	220V AC	8.8	2000	2000	130x130	φ78	60	4	0.55	37

