




受控

PIN	FUNCTION	COLOR	
1	BRAKE (+)	RED	Housing:H68L6-02P Terminal:T68L6-B
2	BRAKE (-)	BLUE	

Connector Detail (Brake Wire)

PIN	FUNCTION	COLOR	
1	MOTOR U	YELLOW	Housing:H68L6-04P Terminal:T68L6-B
2	MOTOR V	RED	
3	MOTOR W	BLACK	
4	MOTOR PE #	YELLOW/GREEN	

Connector Detail (Power Wire)



PIN	FUNCTION	COLOR	
1	VDD	RED	
2	GND	BLACK	
3	MA_P+	BROWN	
4	MA_N-	BLUE	
5	SIO_P+	YELLOW	
6	SIO_N-	GREEN	SC-06

Connector Detail (Feedback Wire)


Brake Data

Static friction	1.5N.m
Voltage	24VDC
Power	7.6W


Technical Data



Performance Curve



S/N:62BUK00YYDDNNNN

REV	K4180212	WVD	SL	18-11-5	DESIGN	DATE	P/N
ECN NO.		DRN	APPD	DATE	WVD	18-11-5	9.6950SS
UNLESS OTHERWISE SPECIFIED					TITLE		
TOLERANCES					Outside Drawing		
DECIMALS:					USED ON		
X ±0.5					SMB05-0029-30MR-00SU		
XX ±0.25					REV		
XXX ±0.1					V1.1		
UNIT: mm							
DO NOT SCALE DRAWING							
FIRST ANGLE PROJECTION					SCALE		
					SHEET		
					OF		
KINCO							

FIRST ANGLE PROJECTION



SCALE SHEET

OF

KINCO